

## Nx1 Multimode Fiber Combiner

<b>Features</b>	
High Coupling Efficiency High Power High stability and reliability	
<b>Application</b>	
Fiber Laser	

### Specification

Port Type	Working Wavelength (nm)	Input pump	Output fiber	Pump Efficiency	Package
				Spec	
2x1	800-1000	105/125 0.15	105/125 0.22	≥85%	3X54 70X12X8
3x1		105/125 0.15	200/220 0.22	≥93%	
3x1		105/125 0.22	125 0.46	≥93%	
3x1		105/125 0.22	200/220 0.22	≥90%	
3x1		105/125 0.22	200/220 0.22	≥88%	
4x1		105/125 0.22	125 0.46	≥90%	
7x1		105/125 0.22	125 0.46	≥90%	
7x1		105/125 0.15	220/242 0.22	≥90%	
7x1		105/125 0.22	200 0.46	≥90%	
7x1		105/125 0.22	400/440 0.22	≥90%	
7x1		105/125 0.22	20/400 0.06/0.46	≥90%	

### Ordering Information

MPC	Port Type	Pump fiber	Output fiber	Length	Package
	2x1 3x1 4x1 7x1	XX:specify	XX:specify	0.8=0.8m 1=1m	3x54 70x12x8